NSN 4820-00-967-2893

Globe Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-967-2893

Pipe Size Accommodated:
1.500 inches 1st end
Flow Control Device:
Disk
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Welded
Renewable Seat Ring Type:
Threaded
Maximum Operating Temp:
1020.0 degrees fahrenheit 1st response
Connection Style:
Socket 1st end
Valve Operation Method:
Manual
Connection Type:
Unthreaded internal pipe 1st end
Features Provided:
Bonnet packing
Maximum Operating Pressure:
maximum operating recounci
6000.0 pounds per square inch 2nd response
· -
6000.0 pounds per square inch 2nd response
6000.0 pounds per square inch 2nd response Material:
6000.0 pounds per square inch 2nd response Material: Stainless steel stem
6000.0 pounds per square inch 2nd response Material: Stainless steel stem Material Specification:
6000.0 pounds per square inch 2nd response Material: Stainless steel stem Material Specification: Astm a182, gr f11 assn standard single material response body
6000.0 pounds per square inch 2nd response Material: Stainless steel stem Material Specification: Astm a182, gr f11 assn standard single material response body Media For Which Designed:
6000.0 pounds per square inch 2nd response Material: Stainless steel stem Material Specification: Astm a182, gr f11 assn standard single material response body Media For Which Designed: Water-oil-gas 2nd response
6000.0 pounds per square inch 2nd response Material: Stainless steel stem Material Specification: Astm a182, gr f11 assn standard single material response body Media For Which Designed: Water-oil-gas 2nd response Surface Treatment:
6000.0 pounds per square inch 2nd response Material: Stainless steel stem Material Specification: Astm a182, gr f11 assn standard single material response body Media For Which Designed: Water-oil-gas 2nd response Surface Treatment: Chromate
6000.0 pounds per square inch 2nd response Material: Stainless steel stem Material Specification: Astm a182, gr f11 assn standard single material response body Media For Which Designed: Water-oil-gas 2nd response Surface Treatment: Chromate Style Designator:
6000.0 pounds per square inch 2nd response Material: Stainless steel stem Material Specification: Astm a182, gr f11 assn standard single material response body Media For Which Designed: Water-oil-gas 2nd response Surface Treatment: Chromate Style Designator: Err-090
6000.0 pounds per square inch 2nd response Material: Stainless steel stem Material Specification: Astm a182, gr f11 assn standard single material response body Media For Which Designed: Water-oil-gas 2nd response Surface Treatment: Chromate Style Designator: Err-090 Shelf Life:
6000.0 pounds per square inch 2nd response Material: Stainless steel stem Material Specification: Astm a182, gr f11 assn standard single material response body Media For Which Designed: Water-oil-gas 2nd response Surface Treatment: Chromate Style Designator: Err-090 Shelf Life: N/a
6000.0 pounds per square inch 2nd response Material: Stainless steel stem Material Specification: Astm a182, gr f11 assn standard single material response body Media For Which Designed: Water-oil-gas 2nd response Surface Treatment: Chromate Style Designator: Err-090 Shelf Life: N/a
Material: Stainless steel stem Material Specification: Astm a182, gr f11 assn standard single material response body Media For Which Designed: Water-oil-gas 2nd response Surface Treatment: Chromate Style Designator: Err-090 Shelf Life: N/a Unit Of Measure:
Material: Stainless steel stem Material Specification: Astm a182, gr f11 assn standard single material response body Media For Which Designed: Water-oil-gas 2nd response Surface Treatment: Chromate Style Designator: Err-090 Shelf Life: N/a Unit Of Measure: Demilitarization: