NSN 4820-00-971-3567

Lift-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-971-3567

Thread Class:

3b all ends

Thread Direction:

Right-hand all ends

Offset Distance:

0.515 inches

Flow Control Device:

Poppet

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Renewable Seat Ring Type:

Pressed-in

Maximum Operating Temp:

160.0 degrees fahrenheit single response

Connection Style:

Gasket seal (boss) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded internal boss all ends

Mounting Position:

Horizontal

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.437 inches all ends

Material:

Steel comp 440c seat

Material Specification:

Qq-s-763, class 44-c, cond a federal specification single material response seat

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf all ends

Shelf Life:

N/a

Unit Of Measure:

--

NSN 4820-00-971-3567

Lift-check Valve - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A530b0

