NSN 4820-00-973-7965

Plug Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-973-7965

| Pipe Size Accommodated: |
|---|
| 0.750 inches 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Flow Style: |
| Three-way two port bottom outlet 90 degree plug turn |
| Maximum Operating Temp: |
| 25.0 degrees fahrenheit single response |
| End Application: |
| Arsr-1, fa-7120 amplitron pwr supply; arsr-2, fa-71710 amplitron pwr supply |
| Connection Style: |
| G9 plain, optional en (pipe) 1st end |
| Valve Operation Method: |
| Manual |
| Connection Type: |
| Threaded internal pipe 1st end |
| Mounting Facility: |
| Bracket |
| Features Provided: |
| Nonadjustable rotation |
| Thready Qty Per Inch (tpi): |
| 14 1st end |
| Maximum Operating Pressure: |
| 90.0 pounds per square inch single response |
| Thread Size: |
| 0.750 inches 1st end |
| Special Features: |
| Mp-4903, instruction book arssr-1d/e/f, vol 5, sec 10, pg 10-755; mp-4441, instruction book, arsr-2, vol 5, sec 10, pg 10-559 |
| Material: |
| Plastic polyamide flow control device |
| Media For Which Designed: |
| Hydrogen 2nd response |
| Surface Treatment: |
| Anodize |
| Thread Series Designator: |
| Npt 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 4820-00-973-7965

Plug Valve - Page 2 of 2



Fiig:

A046b0