NSN 4820-00-977-6248

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-977-6248

Thread Class:
3a all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Disk
Maximum Operating Temp:
275.0 degrees fahrenheit single response
Connection Style:
G42 flared (tube) all ends
Valve Operation Method:
Hydraulic
Connection Type:
Threaded external tube all ends
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
12 all ends
Adjustable Pressure Range:
+155.0/+165.0 pounds per square inch
Maximum Operating Pressure:
10000.0 pounds per square inch single response
Thread Size:
1.875 inches all ends
Seat Angle:
37.0 degrees all ends
Seat Radius:
0.005 inches
Outside Diameter Tube Accommodated:
1.500 inches all ends
Material:
Steel body
Material Specification:
B-113, sun electric corporation mfr ref single material response body
Media For Which Designed:
Hydraulic fluid, mineral base single response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification single treatment response
Style Designator:
Err-090

NSN 4820-00-977-6248

Safety Relief Valve - Page 2 of 2



Unj all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0