NSN 4820-00-979-6415

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-979-6415 **Thread Direction:** Right-hand all ends Flow Control Device: Disk **Bonnet Type:** Inside spring **Bonnet Attachment Method:** Threaded **Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 85.0 cubic feet per minute **Maximum Operating Temp:** 385.0 degrees fahrenheit single response **Connection Style:** G46b plain (pipe) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external pipe all ends **Features Provided:** Valve stem lock shield **Adjustable Pressure Range:** +300.0/+1500.0 pounds per square inch **Maximum Operating Pressure:** 1800.0 pounds per square inch single response **Thread Size:** 0.250 inches all ends **Opening Pressure Setting:** 1500.0 pounds per square inch Material: Stainless steel flow control device Media For Which Designed: Air single response **Style Designator:** Err-090 **Thread Series Designator:** Npt all ends Shelf Life: N/a

--

Unit Of Measure:

NSN 4820-00-979-6415

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0