

View Online at <https://aerobasegroup.com/nsn/4820-00-980-0065>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Pressure seal, ring type

Disk Loading Method:

Spring

Connection Style:

G42 flared (tube) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube 1st end

Thready Qty Per Inch (tpi):

16 1st end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.750 inches 1st end

Seat Angle:

37.0 degrees 1st end

Opening Pressure Setting:

6.0 pounds per square inch

Outside Diameter Tube Accommodated:

0.500 inches 1st end

Media For Which Designed:

Hydraulic fluid, phosphate-ester base single response

Surface Treatment:

Anodize

Style Designator:

Err-090

Test Data Document:

99240-2r2306 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0