

View Online at <https://aerobasegroup.com/nsn/4820-00-983-5928>

**Flange Diameter:**

5.563 inches

**Bonnet Type:**

Outside screw-yoke

**Bonnet Attachment Method:**

Bolted

**Bolt Hole Quantity:**

6

**Valve Operation Method:**

Manual

**Connection Type:**

Flange, round w/holes

**Features Provided:**

Bonnet packing

**Valve Size:**

2.000 inches

**Maximum Operating Pressure And Media For Which Designed:**

150.0 pounds per square inch water-oil-gas

**Stem Type:**

Rising

**Maximum Operating Temperature And Media For Which Designed:**

650.0 degrees fahrenheit water-oil-gas

**Face To Face Distance:**

7.000 inches

**Flange Face Design:**

Plain

**Special Features:**

0.562 in. Thk; 0.563 in. Bolt hole dia; 4.438 in. Bolt circle dia

**Material:**

Stainless steel stem

**Material Specification:**

Mil-r-17131, mil-rcocr-a military specification single material response seat

**Specification Or Standard:**

D composition and 150 psi rating

**Departure From Cited Document:**

As modified by trim matl sr-1 spec/std controlling data cage 81349 nondefinitive govt spec/std ref milv18110 sr-5, the mfr data mfr code 11672 design control ref al117822

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500a0

**Mil-std (military Standard):**

Mil-r-17131 spec.