NSN 4820-00-983-6603

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-983-6603

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Integral

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

1.2 gallons per minute

Connection Style:

G4 gasket sea (boss) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded internal boss 1st end

Mounting Facility:

Threaded fastener

Features Provided:

Valve stem lock shield and bonnet packing and pressure tight outlet side

Thready Qty Per Inch (tpi):

20 1st end

Adjustable Pressure Range:

+1000.0/+2300.0 pounds per square inch

Maximum Operating Pressure:

2300.0 pounds per square inch single response

Thread Size:

0.437 inches 1st end

Media For Which Designed:

Hydraulic fluid, phosphate-ester base single response

Style Designator:

Err-090

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 4820-00-983-6603

Safety Relief Valve - Page 2 of 2

Fiig: A046b0

