NSN 4820-00-984-2575

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-984-2575

| Thread Class: |
|---|
| 3a 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Flow Control Device: |
| Poppet |
| Disk Loading Method: |
| Spring |
| Maximum Operating Temp: |
| 225.0 degrees fahrenheit single response |
| Connection Style: |
| G42 flared (tube) 1st end |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Threaded external tube 1st end |
| Adjustable Pressure Range: |
| +40.0/+125.0 pounds per square inch |
| Maximum Operating Pressure: |
| 3600.0 pounds per square inch single response |
| Thread Size: |
| 0.750 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Material: |
| Stainless steel flow control device |
| Surface Treatment: |
| Anodize |
| Style Designator: |
| Err-090 |
| Thread Series Designator: |
| Unjf 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A046b0 |
| |