NSN 4820-00-987-6278

Globe Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-987-6278

Pipe Size Accommodated:
0.250 inches all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Needle
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Threaded
Maximum Operating Temp:
212.0 degrees fahrenheit single response
Connection Style:
G46b plain (pipe) all ends
Valve Operation Method:
Manual
Connection Type:
Threaded external pipe all ends
Features Provided:
Bonnet packing
Maximum Operating Pressure:
Maximum Operating Pressure: 4500.0 pounds per square inch single response
· · ·
4500.0 pounds per square inch single response
4500.0 pounds per square inch single response Thread Size:
4500.0 pounds per square inch single response Thread Size: 0.250 inches all ends
4500.0 pounds per square inch single response Thread Size: 0.250 inches all ends Material:
4500.0 pounds per square inch single response Thread Size: 0.250 inches all ends Material: Stainless steel stem
4500.0 pounds per square inch single response Thread Size: 0.250 inches all ends Material: Stainless steel stem Media For Which Designed:
4500.0 pounds per square inch single response Thread Size: 0.250 inches all ends Material: Stainless steel stem Media For Which Designed: Hydraulic fluid, phosphate-ester base 2nd response
4500.0 pounds per square inch single response Thread Size: 0.250 inches all ends Material: Stainless steel stem Media For Which Designed: Hydraulic fluid, phosphate-ester base 2nd response Style Designator:
4500.0 pounds per square inch single response Thread Size: 0.250 inches all ends Material: Stainless steel stem Media For Which Designed: Hydraulic fluid, phosphate-ester base 2nd response Style Designator: Err-090
4500.0 pounds per square inch single response Thread Size: 0.250 inches all ends Material: Stainless steel stem Media For Which Designed: Hydraulic fluid, phosphate-ester base 2nd response Style Designator: Err-090 Thread Series Designator:
4500.0 pounds per square inch single response Thread Size: 0.250 inches all ends Material: Stainless steel stem Media For Which Designed: Hydraulic fluid, phosphate-ester base 2nd response Style Designator: Err-090 Thread Series Designator: Nptf all ends
4500.0 pounds per square inch single response Thread Size: 0.250 inches all ends Material: Stainless steel stem Media For Which Designed: Hydraulic fluid, phosphate-ester base 2nd response Style Designator: Err-090 Thread Series Designator: Nptf all ends Shelf Life:
4500.0 pounds per square inch single response Thread Size: 0.250 inches all ends Material: Stainless steel stem Media For Which Designed: Hydraulic fluid, phosphate-ester base 2nd response Style Designator: Err-090 Thread Series Designator: Nptf all ends Shelf Life: N/a
4500.0 pounds per square inch single response Thread Size: 0.250 inches all ends Material: Stainless steel stem Media For Which Designed: Hydraulic fluid, phosphate-ester base 2nd response Style Designator: Err-090 Thread Series Designator: Nptf all ends Shelf Life: N/a
4500.0 pounds per square inch single response Thread Size: 0.250 inches all ends Material: Stainless steel stem Media For Which Designed: Hydraulic fluid, phosphate-ester base 2nd response Style Designator: Err-090 Thread Series Designator: Nptf all ends Shelf Life: N/a Unit Of Measure:
4500.0 pounds per square inch single response Thread Size: 0.250 inches all ends Material: Stainless steel stem Media For Which Designed: Hydraulic fluid, phosphate-ester base 2nd response Style Designator: Err-090 Thread Series Designator: Nptf all ends Shelf Life: N/a Unit Of Measure: Demilitarization: