NSN 4820-00-988-9878

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-988-9878

| | Ŭ |
|--|---|
| Thread Class: | |
| 3b 2nd end | |
| Thread Direction: | |
| Right-hand all ends | |
| Flow Control Device: | |
| Disk | |
| Disk Loading Method: | |
| Spring | |
| Maximum Operating Temp: | |
| 275.0 degrees fahrenheit single response | |
| Connection Style: | |
| G42 flared (tube) 1st end | |
| Valve Operation Method: | |
| Automatic | |
| Connection Type: | |
| Threaded internal tube 2nd end | |
| Features Provided: | |
| Pressure tight outlet side | |
| Maximum Operating Pressure: | |
| 150.0 pounds per square inch single response | |
| Thread Size: | |
| 0.562 inches all ends | |
| Seat Angle: | |
| 37.0 degrees 1st end | |
| Opening Pressure Setting: | |
| 75.0 pounds per square inch | |
| Outside Diameter Tube Accommodated: | |
| 0.375 inches 2nd end | |
| Material: | |
| Stainless steel seat | |
| Style Designator: | |
| Err-090 | |
| Thread Series Designator: | |
| Unf all ends | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A046b0 | |
| | |