

View Online at <https://aerobasegroup.com/nsn/4820-00-989-5048>

Flow Control Device:

Needle

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

850.0 degrees fahrenheit single response

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Bonnet packing

Maximum Operating Pressure:

600.0 pounds per square inch single response

Outside Diameter:

3.375 inches all ends

Face To Face Distance:

5.500 inches

Thickness:

0.562 inches all ends

Bolt Hole Diameter:

0.562 inches all ends

Bolt Circle Diameter:

2.250 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.250 inches all ends

Raised Face Diameter:

1.250 inches all ends

Material:

Steel

Material Specification:

Mil-r-17131, mil-rcocr-a military specification single material response seat

Media For Which Designed:

Steam single response

Style Designator:

Err-090

Specification Or Standard:

B composition and pressure 600 rating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A046b0

Mil-std (military Standard):

Mil-r-17131 spec.