

View Online at <https://aerobasegroup.com/nsn/4820-00-989-5446>

Body Material:

Brass

Outside Surface Treatment:

Any acceptable

Body Style:

Straight thru

Furnished Items:

Inlet pressure gage and outlet pressure gage

Media For Which Designed:

Argon and nitrogen, liquid

First End Connection Type:

Threaded internal gas cylinder

First End Style Designator:

Swivel nut, gas

First End Thread Size And Series/type Designator:

0.965-14 ngo

First End Thread Direction:

Left-hand

Second End Relationship With First End:

Not identical

Second End Connection Type:

Threaded external boss

Second End Style Designator:

Swivel nut, flared

Second End Thread Size And Series/type Designator:

9/16-18 unf

Second End Thread Class:

2a

Second End Thread Direction:

Left-hand

Seat Material:

Brass

Flow Control Device:

Disk, flat, top and bottom guided

Flow Control Device Material:

Nonmetallic

End Connection Quantity:

2

First End Thread Pitch Diameters:

Any acceptable

Outlet Pressure Range:

+0.0/+60.0 pounds per square inch

Regulation Type:

1st stage automatic, 2nd stage manual

Manual Control Method:

Screw

Valve Stem Design:

Single seat

Valve Loading Method:

Spring

Maximum Inlet Pressure Rating:

4000.0 pounds per square inch

Outlet Pressure Accuracy Rating:

Not rated

Filter:

Included

Unable To Decode:

Unable to decode and unable to decode

Unable To Decode:

Unable to decode and unable to decode

Temperature Rating:

Between -40.0 degrees fahrenheit and 165.0 degrees fahrenheit

Special Features:

16.7cfm, max flow capacity maximum rated inlet and outletpressure, 40 microns, smallest particles removed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A21100