NSN 4820-00-989-8019

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-989-8019

Pipe Size Accommodated:
0.250 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Maximum Operating Temp:
400.0 degrees fahrenheit single response
End Application:
Lgm-30 minuteman missle.
Connection Style:
G9 plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Valve stem lock shield and pressure tight outlet side
Maximum Operating Pressure:
33.0 pounds per square inch single response
Thread Size:
0.250 inches 2nd end
Opening Pressure Setting:
300.0 pounds per square inch
Material:
Copper alloy body
Media For Which Designed:
Gas, natural 2nd response
Style Designator:
Err-090
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-989-8019

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0