

View Online at <https://aerobasegroup.com/nsn/4820-00-990-8393>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

850.0 degrees fahrenheit single response

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Bonnet packing

Maximum Operating Pressure:

600.0 pounds per square inch single response

Outside Diameter:

5.250 inches all ends

Thickness:

0.812 inches all ends

First Connection Face To Centerline Distance:

4.500 inches

Bolt Hole Diameter:

0.687 inches all ends

Second Connection Face To Centerline Distance:

4.500 inches

Bolt Circle Diameter:

3.875 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.250 inches all ends

Raised Face Diameter:

2.500 inches all ends

Material:

Stainless steel stem

Material Specification:

Astma182, gradef11 assn standard single material response body

Media For Which Designed:

Steam single response

Style Designator:

Err-090

Specification Or Standard:

B composition and 600 rating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0