

View Online at <https://aerobasegroup.com/nsn/4820-00-991-9830>

**Thread Class:**

3b

**Flow Control Device:**

Ported rotor

**End Application:**

T.O. 9h8-14-226-3; u/o c130 acft; u/o code d

**Valve Operation Method:**

Manual

**Connection Quantity:**

3

**Connection Type:**

Threaded internal boss

**Mounting Facility:**

Sub-plate

**Connection Location:**

Side

**Valve Size:**

0.750 inches

**Flow Type:**

Three-way

**Thready Qty Per Inch (tpi):**

12

**Maximum Operating Pressure And Media For Which Designed:**

3000.0 pounds per square inch hydraulic fluid, petroleum base

**Thread Size:**

1.063 inches

**Body Material:**

Aluminum alloy

**Maximum Operating Temperature And Media For Which Designed:**

160.0 degrees fahrenheit hydraulic fluid, petroleum base

**Special Features:**

Manufacturers suggested name is selector valve, 3 way-2 position, hydraulic; proof pressure 4500 psi; burst pressure 7500 psi; rated flow 18 gpm; temperature range -65 to +160 degrees feh; conforms to mil-v-5529a; fluid mil-h-46170; weight 1 3/4 lbs; ports per ms33649-12; finish per mil-a-8625

**Thread Series Designator:**

Unj

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A501t0