

View Online at <https://aerobasegroup.com/nsn/4820-00-991-9830>

Thread Class:

3b

Flow Control Device:

Ported rotor

End Application:

T.O. 9h8-14-226-3; u/o c130 acft; u/o code d

Valve Operation Method:

Manual

Connection Quantity:

3

Connection Type:

Threaded internal boss

Mounting Facility:

Sub-plate

Connection Location:

Side

Valve Size:

0.750 inches

Flow Type:

Three-way

Thready Qty Per Inch (tpi):

12

Maximum Operating Pressure And Media For Which Designed:

3000.0 pounds per square inch hydraulic fluid, petroleum base

Thread Size:

1.063 inches

Body Material:

Aluminum alloy

Maximum Operating Temperature And Media For Which Designed:

160.0 degrees fahrenheit hydraulic fluid, petroleum base

Special Features:

Manufacturers suggested name is selector valve, 3 way-2 position, hydraulic; proof pressure 4500 psi; burst pressure 7500 psi; rated flow 18 gpm; temperature range -65 to +160 degrees feh; conforms to mil-v-5529a; fluid mil-h-46170; weight 1 3/4 lbs; ports per ms33649-12; finish per mil-a-8625

Thread Series Designator:

Unj

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A501t0