## NSN 4820-00-998-7752

Angle Valve - Page 1 of 2

Flow Control Device:

**Bonnet Type:** 

Disk



View Online at https://aerobasegroup.com/nsn/4820-00-998-7752

Inside screw
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
6 2nd end
Valve Operation Method:
Manual
Flange Shape:
Round with holes 2nd end
Connection Type:
Flange 1st end
Features Provided:
Bonnet packing
Valve Size:
2.000 inches
Maximum Operating Pressure:
300.0 pounds per square inch single response
Outside Diameter:
5.562 inches 2nd end
Thickness:
0.750 inches 2nd end
First Connection Face To Centerline Distance:
6.250 inches
Bolt Hole Diameter:
0.687 inches 1st end
Second Connection Face To Centerline Distance:
4.875 inches
Bolt Circle Diameter:
5.187 inches 1st end
5.187 inches 1st end Flange Face Design:
Flange Face Design:
Flange Face Design: Plain 2nd end
Flange Face Design: Plain 2nd end Raised Face Height:
Flange Face Design: Plain 2nd end Raised Face Height: 0.062 inches 1st end
Flange Face Design: Plain 2nd end Raised Face Height: 0.062 inches 1st end Raised Face Diameter:
Flange Face Design: Plain 2nd end Raised Face Height: 0.062 inches 1st end Raised Face Diameter: 3.625 inches 1st end
Flange Face Design: Plain 2nd end Raised Face Height: 0.062 inches 1st end Raised Face Diameter: 3.625 inches 1st end Material:
Flange Face Design: Plain 2nd end Raised Face Height: 0.062 inches 1st end Raised Face Diameter: 3.625 inches 1st end Material: Nickel alloy body

## NSN 4820-00-998-7752

Angle Valve - Page 2 of 2

A046b0



Style Designator:
Err-090
Reference Number Differentiating Characteristics:
As differentiated and amended by spcc specification 4820-00-9987752 for sub-safe items
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: