## NSN 4820-01-003-7391

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-003-7391 **Thread Direction:** Right-hand 1st end **Flow Control Device: Poppet Bonnet Type:** Inside spring **Bonnet Attachment Method:** Integral **Disk Loading Method:** Spring **Maximum Operating Temp:** 280.0 degrees fahrenheit single response **Connection Style:** G46b plain (pipe) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded external pipe 1st end **Maximum Operating Pressure:** 200.0 pounds per square inch single response **Thread Size:** 0.125 inches 1st end **Opening Pressure Setting:** 80.0 pounds per square inch Material: Aluminum alloy 2024 body **Material Specification:** Qq-a-225/6 federal specification single material response body Media For Which Designed: Fuel/oil, hydrocarbon single response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response **Style Designator:** Err-090 **Thread Series Designator:** Npt 1st end Shelf Life: N/a

**Unit Of Measure:** 

## NSN 4820-01-003-7391

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.