NSN 4820-01-003-7392

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-003-7392

| View Online at https://aerobasegroup.com/nsn/4820-01-003-7392 |
|---|
| Thread Direction: |
| Right-hand 1st end |
| Flow Control Device: |
| Poppet |
| Bonnet Type: |
| Inside spring |
| Bonnet Attachment Method: |
| Integral |
| Disk Loading Method: |
| Spring |
| Maximum Operating Temp: |
| 280.0 degrees fahrenheit single response |
| Connection Style: |
| G46b plain (pipe) 1st end |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Threaded external pipe 1st end |
| Maximum Operating Pressure: |
| 200.0 pounds per square inch single response |
| Thread Size: |
| 0.125 inches 1st end |
| Opening Pressure Setting: |
| 32.0 pounds per square inch |
| Material: |
| Aluminum alloy 2024 body |
| Material Specification: |
| Qq-a-225/6 federal specification single material response body |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625, type 1 military specification single treatment response |
| Style Designator: |
| Err-090 |
| Thread Series Designator: |
| Npt 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 4820-01-003-7392

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.

