## NSN 4820-01-004-0774

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-004-0774 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Maximum Operating Temp:** 350.0 degrees fahrenheit single response **Connection Style:** Flared (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 260.0 pounds per square inch single response **Thread Size:** 0.438 inches all ends Seat Angle: 37.0 degrees 1st end **Outside Diameter Tube Accommodated:** 0.250 inches 1st end Material: Aluminum alloy 2024 **Material Specification:** Qq-a-225/6, alloy 2024 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response **Style Designator:** Straight thru **Thread Series Designator:** Unjf all ends Shelf Life: N/a **Unit Of Measure:** 

Unit Of Measure:
-Demilitarization:
No

## NSN 4820-01-004-0774

Check Valve - Page 2 of 2



Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.