

View Online at <https://aerobasegroup.com/nsn/4820-01-006-8586>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

975.0 degrees fahrenheit single response

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Maximum Operating Pressure:

1500.0 pounds per square inch single response

Outside Diameter:

5.875 inches all ends

Face To Face Distance:

10.000 inches

Thickness:

1.125 inches all ends

Bolt Hole Diameter:

1.000 inches all ends

Bolt Circle Diameter:

4.000 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.250 inches all ends

Raised Face Diameter:

2.000 inches all ends

Special Features:

Stgn valve type; centerless ground and hardened stems

Material:

Steel stem

Material Specification:

Astm a105, grade 2 assn standard single material response flow control device

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

Err-090

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0