## NSN 4820-01-008-1771

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-008-1771 **Thread Class:** 2b 3rd end **Thread Direction:** Right-hand 1st end Flow Control Device: Disk **Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 30.0 gallons per minute **Maximum Operating Temp:** 225.0 degrees fahrenheit single response **Connection Style:** G4 gasket sea (boss) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss 3rd end **Mounting Facility: Bracket** Thready Qty Per Inch (tpi): 12 1st end Adjustable Pressure Range: +300.0/+3000.0 pounds per square inch **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.875 inches 3rd end **Special Features:** Furnished with end fittings and o-rings Material: Steel stem Media For Which Designed: Fuel/oil, hydrocarbon single response **Style Designator:** Err-090 **Thread Series Designator:** Unf 3rd end Shelf Life: N/a

**Unit Of Measure:** 

## NSN 4820-01-008-1771

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0