

View Online at <https://aerobasegroup.com/nsn/4820-01-008-3150>

Thread Class:

3b 2nd end

Thread Direction:

Right-hand 2nd end

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

135.0 degrees fahrenheit 2nd response

Connection Style:

Grooved (tube) 1st end

Valve Operation Method:

Automatic

Connection Type:

Unthreaded external tube 1st end

Mounting Position:

Horizontal or vertical

Thready Qty Per Inch (tpi):

12 2nd end

Maximum Operating Pressure:

60.0 pounds per square inch single response

Thread Size:

1.875 inches 2nd end

Outside Diameter Tube Accommodated:

1.500 inches 1st end

Material:

Stainless steel flow control device

Material Specification:

Qq-a-225/8, alloy 6061, t651 federal specification single material response body

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Straight thru

Thread Series Designator:

Unj 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.