

View Online at <https://aerobasegroup.com/nsn/4820-01-008-3150>

**Thread Class:**

3b 2nd end

**Thread Direction:**

Right-hand 2nd end

**Flow Control Device:**

Poppet

**Disk Loading Method:**

Spring

**Maximum Operating Temp:**

135.0 degrees fahrenheit 2nd response

**Connection Style:**

Grooved (tube) 1st end

**Valve Operation Method:**

Automatic

**Connection Type:**

Unthreaded external tube 1st end

**Mounting Position:**

Horizontal or vertical

**Thready Qty Per Inch (tpi):**

12 2nd end

**Maximum Operating Pressure:**

60.0 pounds per square inch single response

**Thread Size:**

1.875 inches 2nd end

**Outside Diameter Tube Accommodated:**

1.500 inches 1st end

**Material:**

Stainless steel flow control device

**Material Specification:**

Qq-a-225/8, alloy 6061, t651 federal specification single material response body

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Style Designator:**

Straight thru

**Thread Series Designator:**

Unj 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530b0

**Mil-std (military Standard):**

Mil-a-8625 spec.