## NSN 4820-01-010-1599

Poppet Drain Cock - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-010-1599 **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Maximum Operating Temp:** 160.0 degrees fahrenheit single response **Connection Style:** Gasket seal (boss) 2nd end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss 2nd end **Maximum Operating Pressure:** 200.0 pounds per square inch 1st response **Thread Size:** 0.562 inches 2nd end Seat Angle: 12.0 degrees 1st end **Outside Diameter Tube Accommodated:** 0.375 inches 2nd end **Special Features:** Second end free flowing and maximum altitude of 45, 000 ft. Material: Stainless steel stem Media For Which Designed: Fuel/oil, hydrocarbon single response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response **Style Designator:** Straight thru **Thread Series Designator:** Unf 2nd end Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 4820-01-010-1599

Poppet Drain Cock - Page 2 of 2



Fiig:

A530c0

Mil-std (military Standard):

Mil-a-8625 spec.