NSN 4820-01-011-6156

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-011-6156

Thread Class:
3a all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Maximum Operating Temp:
225.0 degrees fahrenheit single response
Connection Style:
G42 flared (tube) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube all ends
Adjustable Pressure Range:
+10.0/+50.0 pounds per square inch
Maximum Operating Pressure:
50.0 pounds per square inch single response
Thread Size:
0.438 inches all ends
Seat Angle:
37.0 degrees all ends
Opening Pressure Setting:
35.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.250 inches all ends
Material:
Steel comp 303 flow control device
Material Specification:
Qq-b-626, alloy 360 federal specification single material response body
Media For Which Designed:
Air 1st response
Style Designator:
Err-090
Thread Series Designator:
Unjf all ends

NSN 4820-01-011-6156

Safety Relief Valve - Page 2 of 2



_			-		
C	hο	14		.ife	
•			_	.II C	-

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0