

View Online at <https://aerobasegroup.com/nsn/4820-01-011-6579>

**Thread Class:**

3a all ends

**Thread Direction:**

Right-hand all ends

**Flow Control Device:**

Poppet

**Disk Loading Method:**

Spring

**Valve Discharge Flow Rate:**

2.5 gallons per minute

**Maximum Operating Temp:**

225.0 degrees fahrenheit single response

**Connection Style:**

G42 flared (tube) all ends

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded external tube all ends

**Adjustable Pressure Range:**

+10.0/+50.0 pounds per square inch

**Maximum Operating Pressure:**

50.0 pounds per square inch single response

**Thread Size:**

0.438 inches all ends

**Seat Angle:**

37.0 degrees all ends

**Opening Pressure Setting:**

35.0 pounds per square inch

**Outside Diameter Tube Accommodated:**

0.250 inches all ends

**Material:**

Steel comp 303 flow control device

**Material Specification:**

Fed standard 66, aisi 303/sae 30303 federal standard single material response flow control device

**Media For Which Designed:**

Fuel/oil, hydrocarbon 1st response

**Surface Treatment:**

Passivate

**Style Designator:**

Err-090

**Thread Series Designator:**

Unjf all ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0