NSN 4820-01-013-8987

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-013-8987

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

400.0 degrees fahrenheit single response

Connection Style:

G46b plain (pipe) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded external pipe 1st end

Adjustable Pressure Range:

+0.5/+200.0 pounds per square inch

Maximum Operating Pressure:

200.0 pounds per square inch single response

Thread Size:

0.375 inches 1st end

Opening Pressure Setting:

20.0 pounds per square inch

Material:

Aluminum alloy 2024 body

Material Specification:

Qq-a-225/6, alloy 2024 federal specification single material response seat

Media For Which Designed:

Water-oil-gas single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

Style Designator:

Err-090

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 4820-01-013-8987

Safety Relief Valve - Page 2 of 2

Fiig: A046b0

Mil-std (military Standard):

Mil-a-8625 spec.

