## NSN 4820-01-018-1823

Check Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-018-1823

| Thread Direction:                             |
|---|
| Right-hand all ends                           |
| Flow Control Device:                          |
| Disk  |
| Disk Loading Method:                          |
| Spring  |
| Maximum Operating Temp:                       |
| 225.0 degrees fahrenheit single response      |
| Connection Style:                             |
| Plain (screw-in cartridge) all ends           |
| Valve Operation Method:                       |
| Automatic                                     |
| Connection Type:                              |
| Threaded cartridge all ends                   |
| Mounting Position:                            |
| Horizontal or vertical                        |
| Maximum Operating Pressure:                   |
| 6000.0 pounds per square inch single response |
| Thread Size:                                  |
| 1.000 inches all ends                         |
| Special Features:                             |
| Cartridge type                                |
| Material:                                     |
| Nickel alloy r-405 seat                       |
| Media For Which Designed:                     |
| Water-oil-gas single response                 |
| Style Designator:                             |
| Screw-in cartridge                            |
| Thread Series Designator:                     |
| Npt all ends                                  |
| Shelf Life:                                   |
| N/a   |
| Unit Of Measure:                              |
|   |
| Demilitarization:                             |
| No  |
| Fiig:   |
| A530b0  |
|   |