9-3293



up.com/nsn/4820-01-019-3293

NSN 4820-01-019-3293 Safety Relief Valve - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/4
Thread Class:
2b all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
100.0 gallons per minute
End Application:
Gruman a-10 aircraft
Connection Style:
G4 gasket sea (boss) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss all ends
Mounting Facility:
Threaded fastener
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
12 all ends
Adjustable Pressure Range:
+50.0/+500.0 pounds per square inch
Maximum Operating Pressure:
4000.0 pounds per square inch single response
Thread Size:
1.625 inches all ends

1.625 inches all ends

Material:

Steel flow control device

Media For Which Designed:

Oil, hydraulic single response

Surface Treatment:

Anodize

Style Designator:

Err-090

Thread Series Designator:

Un all ends

Shelf Life:

N/a

NSN 4820-01-019-3293

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

