NSN 4820-01-019-4650



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-01-019-4650 **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 280.0 degrees fahrenheit single response **Minimum Operating Temp:** -40.0 degrees fahrenheit **Connection Style:** G46a plain (tube) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube 1st end **Maximum Operating Pressure:** 200.0 pounds per square inch single response **Thread Size:** 0.438 inches 1st end **Opening Pressure Setting:** 3.0 pounds per square inch Material: Aluminum alloy 2024 **Material Specification:** Qq-a-250/4, alloy 2024, t351 federal specification single material response Media For Which Designed: Helium 5th response **Style Designator:** Err-090 **Thread Series Designator:** Unjf 1st end **Furnished Items And Quantity:** 1 deflector cap Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 4820-01-019-4650

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0