## NSN 4820-01-020-7102

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-020-7102

| Thread Direction:                             |
|---|
| Right-hand all ends                           |
| Flow Control Device:                          |
| Poppet  |
| Disk Loading Method:                          |
| Spring  |
| Connection Style:                             |
| G9 plain, optional en (pipe) all ends         |
| Valve Operation Method:                       |
| Automatic                                     |
| Connection Type:                              |
| Threaded internal pipe all ends               |
| Features Provided:                            |
| Pressure tight outlet side                    |
| Maximum Operating Pressure:                   |
| 2500.0 pounds per square inch single response |
| Thread Size:                                  |
| 0.500 inches all ends                         |
| Material:                                     |
| Steel stem                                    |
| Media For Which Designed:                     |
| Oil single response                           |
| Surface Treatment:                            |
| Anodize                                       |
| Style Designator:                             |
| Err-090                                       |
| Thread Series Designator:                     |
| Nptf all ends                                 |
| Shelf Life:                                   |
| N/a   |
| Unit Of Measure:                              |
|   |
| Demilitarization:                             |
| No  |
| Fiig:   |
| A046b0  |
|   |
|   |