## NSN 4820-01-021-0628

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-021-0628 **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 280.0 degrees fahrenheit single response **Connection Style:** G46a plain (tube) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube 1st end **Maximum Operating Pressure:** 200.0 pounds per square inch single response **Thread Size:** 0.750 inches 1st end **Opening Pressure Setting:** 20.0 pounds per square inch Material: Aluminum alloy 2024 body **Material Specification:** Qq-a-225/6 federal specification single material response body **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response **Style Designator:** Err-090 **Thread Series Designator:** Unjf 1st end Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A046b0

## NSN 4820-01-021-0628

Safety Relief Valve - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.