## NSN 4820-01-021-7735

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-021-7735

Thread Direction:
Right-hand all ends
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Threaded
Maximum Operating Temp:
550.0 degrees fahrenheit single response
Connection Style:
G9 plain, optional en (pipe) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe all ends
Features Provided:
Pressure tight outlet side
Adjustable Pressure Range:
+0.0/+400.0 pounds per square inch
Maximum Operating Pressure:
400.0 pounds per square inch single response
Thread Size:
1.250 inches 1st end
Opening Pressure Setting:
165.0 pounds per square inch
Material:
Steel comp 316
Material Specification:
Fed standard 66, aisi 316/sae 30316 federal standard single material response
Style Designator:
Err-090
Thread Series Designator:
Npt all ends
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4820-01-021-7735

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0