NSN 4820-01-022-3870

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-022-3870

| Pipe Size Accommodated: |
|---|
| 1.500 inches 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Flow Control Device: |
| Disk |
| Bonnet Type: |
| Inside spring |
| Bonnet Attachment Method: |
| Threaded |
| Disk Loading Method: |
| Spring |
| Valve Discharge Flow Rate: |
| 1200.0 pounds per hour |
| Connection Style: |
| G9 plain, optional en (pipe) 1st end |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Threaded internal pipe 1st end |
| Features Provided: |
| Pressure tight outlet side |
| Power Drive Operating Pressure: |
| 15.0 pounds per square inch |
| Maximum Operating Pressure: |
| 15.0 pounds per square inch single response |
| Thread Size: |
| 1.250 inches 2nd end |
| Opening Pressure Setting: |
| 15.0 pounds per square inch |
| Material: |
| Rubber chloroprene class cr seat |
| Media For Which Designed: |
| Steam single response |
| Style Designator: |
| Err-090 |
| Thread Series Designator: |
| Npt 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 4820-01-022-3870

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0