NSN 4820-01-022-3871



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-01-022-3871 **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring Valve Discharge Flow Rate: 4.0 gallons per minute **Renewable Seat Ring Type:** Pressed-in **Maximum Operating Temp:** 300.0 degrees fahrenheit single response **Connection Style:** G9 plain, optional en (pipe) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal pipe all ends **Features Provided:** Pressure tight outlet side **Power Drive Operating Pressure:** 2000.0 pounds per square inch **Adjustable Pressure Range:** +2000.0/+3100.0 pounds per square inch **Maximum Operating Pressure:** 3100.0 pounds per square inch single response **Thread Size:** 0.250 inches all ends **Opening Pressure Setting:** 2600.0 pounds per square inch Material: Steel flow control device **Surface Treatment: Passivate**

Style Designator:
Err-090
Thread Series Designator:
Npt all ends
Shelf Life:
N/a
Unit Of Measure:

NSN 4820-01-022-3871

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0