NSN 4820-01-022-5685

Calibrated Flow Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-022-5685

View Online at https://aerobasegroup.com/nsn/4820-01-022-5685
Body Material:
Aluminum alloy
Outside Surface Treatment:
Anodized
Body Style:
Тее
Furnished Items:
Automatic relief valve
Media For Which Designed:
Hydraulic oil
First End Connection Type:
Threaded internal pipe
First End Style Designator:
Plain
First End Thread Size And Series/type Designator:
0.750-14 nptf
First End Thread Direction:
Right-hand
Second End Relationship With First End:
Identical
Third End Relationship With Preceding Ends:
Not identical with first or second end
Third End Connection Type:
Threaded internal pipe
Third End Style Designator:
Plain
Third End Thread Size And Series/type Designator:
0.375-18 nptf
Third End Thread Direction:
Right-hand
Center To Center Distance:
1.000 inches
Flow Control Device:
Piston, spring loaded
Flow Control Device Material:
Steel
End Connection Quantity:
3
Valve Discharge Flow Rate:
7.0 gallons per minute
Mounting Facility:
Bolts

NSN 4820-01-022-5685

Calibrated Flow Valve - Page 2 of 2

Regulation Type:

Automatic single stage

Maximum Inlet Pressure Rating:

2000.0 pounds per square inch

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A21100

