

View Online at <https://aerobasegroup.com/nsn/4820-01-022-8617>

Body Material:

Aluminum alloy 355-t6 ams4215

Outside Surface Treatment:

Anodized mil-a-8625 type 2 cl 1

Body Style:

Angle

Media For Which Designed:

Hydraulic fluid, mil-h-5606

First End Connection Type:

Threaded internal tube

First End Style Designator:

Gasket seal

First End Outside Diameter Tube Accommodated:

0.750 inches

First End Thread Size And Series/type Designator:

1.062-12 unj

First End Thread Class:

3b

First End Thread Direction:

Right-hand

Second End Relationship With First End:

Identical

Seat Material:

Aluminum alloy 355-t6 ams4215

First End Seat Angle In Deg:

60.0

Packing Material:

Rubber, synthetic, mil-p-25732

Flow Control Device:

Poppet

Flow Control Device Material:

Steel, ams 5630

End Connection Quantity:

2

Mounting Facility:

External thread

Outlet Pressure Range:

+1950.0/+3190.0 pounds per square inch

Regulation Type:

Automatic single stage

Valve Loading Method:

Spring

Maximum Inlet Pressure Rating:

3500.0 pounds per square inch

Outlet Pressure Accuracy Rating:

Not rated

Filter:

Not included

Temperature Rating:

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

Reference Number Differentiating Characteristics:

As differentiated by the source control dwg no.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A21100