NSN 4820-01-023-9905

Calibrated Flow Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-023-9905

Body Material:
Aluminum alloy
Outside Surface Treatment:
Anodized
Body Style:
Straight thru
Media For Which Designed:
Hydraulic oil
First End Connection Type:
Plain face flange
First End Style Designator:
Plain
First End Flange Shape Style:
Rectangular (includes square) w/ bolt holes
First End Flange Thickness:
Any acceptable
First End Flange Length:
5.750 inches
First End Flange Width:
3.500 inches
First End Bolt Hole Quantity:
4
First End Bolt Hole Diameter:
0.350 inches
Second End Relationship With First End:
Identical
Center To Center Distance:
2.000 inches
Flow Control Device:
Piston, spring loaded
Flow Control Device Material:
Steel, corrosion resisting
End Connection Quantity:
2
Valve Discharge Flow Rate:
26.0 gallons per minute
Regulation Type:
Automatic single stage
Maximum Inlet Pressure Rating:
Not rated
First End Center To Center Distance Between Holes Along Length:
3.000 inches

NSN 4820-01-023-9905

Calibrated Flow Valve - Page 2 of 2



First End Center To Center Distance Between Holes Along Width:

2.625 inches

Special Features:

Both end connection in single flange for sub-plate mtg

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A21100