
# NSN 4820-01-024-2816

Safety Relief Valve - Page 1 of 2





Pipe Size Accommodated:

0.750 inches 1st end

### **Flow Control Device:**

Disk

# Bonnet Type:

Inside spring

# **Bonnet Attachment Method:**

Threaded

# **Disk Loading Method:**

Spring

#### Valve Discharge Flow Rate:

104.0 cubic feet per minute

#### **Renewable Seat Ring Type:**

Pressed-in

#### Maximum Operating Temp:

165.0 degrees fahrenheit single response

#### **End Application:**

Witchita class aor

#### **Connection Style:**

Socket (tube) err-100

### Valve Operation Method:

Automatic

#### **Connection Type:**

Unthreaded internal pipe 2nd end

#### **Features Provided:**

Pressure tight outlet side and valve stem lock shield

#### Adjustable Pressure Range:

+71.0/+91.0 pounds per square inch

#### Maximum Operating Pressure:

440.0 pounds per square inch single response

#### Material:

Steel comp 304 seat

#### Material Specification:

Qq-c-390, alloy d4/d/ federal specification single material response body

#### Media For Which Designed:

Air single response

#### Style Designator:

Err-090

### **Furnished Items And Quantity:**

2 nut and 2 tailpiece

#### **Specification Data:**

81349-mil-v-22549 government specification

# NSN 4820-01-024-2816

Safety Relief Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A046b0

# Mil-std (military Standard):

Mil-v-22549 spec.

