NSN 4820-01-025-0341



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-01-025-0341 Flow Control Device: Disk **Bonnet Type:** Inside spring **Bonnet Attachment Method:** Threaded **Disk Loading Method:** Spring **Maximum Operating Temp:** 165.0 degrees fahrenheit single response **End Application:** Ship, ohio class ss (trident) **Connection Style:** Socket with brazing ring (tube) err-100 **Valve Operation Method:** Automatic **Connection Type:** Unthreaded internal tube 1st end **Features Provided:** Pressure tight outlet side **Adjustable Pressure Range:** +2901.0/+5000.0 pounds per square inch **Maximum Operating Pressure:** 5000.0 pounds per square inch single response **Outside Diameter Tube Accommodated:** 0.500 inches 2nd end Material: Steel comp 304 body **Material Specification:** Fed standard 66, aisi 304/sae 30304 federal standard single material response body Media For Which Designed: Air single response **Style Designator:** Err-090 **Furnished Items And Quantity:** 2 nut and 2 tailpiece Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 4820-01-025-0341

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0