## NSN 4820-01-025-7156

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-025-7156 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 160.0 degrees fahrenheit 2nd response **Connection Style:** Flareless all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Mounting Position:** Horizontal or vertical Thready Qty Per Inch (tpi): 12 all ends **Maximum Operating Pressure:** 1500.0 pounds per square inch single response **Thread Size:** 1.625 inches all ends Seat Angle: 12.0 degrees all ends Material: Steel flow control device Media For Which Designed: Hydraulic fluid, phosphate-ester base single response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response **Style Designator:** Straight thru **Thread Series Designator:** Unj all ends Shelf Life: N/a

**Unit Of Measure:** 

## NSN 4820-01-025-7156

Check Valve - Page 2 of 2



Demi		

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.