NSN 4820-01-026-2245

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-026-2245

| Flow Control Device: |
|--|
| Disk |
| Disk Loading Method: |
| Spring |
| Valve Discharge Flow Rate: |
| 463.0 gallons per minute |
| Bolt Hole Quantity: |
| 8 all ends |
| End Application: |
| Marine hardware and hull doors |
| Valve Operation Method: |
| Automatic |
| Flange Shape: |
| Round with holes all ends |
| Connection Type: |
| Flange all ends |
| Valve Size: |
| 3.000 inches |
| Opening Pressure Setting: |
| 25.0 pounds per square inch |
| Outside Diameter: |
| 6.625 inches all ends |
| Thickness: |
| 0.500 inches all ends |
| First Connection Face To Centerline Distance: |
| 4.000 inches |
| Bolt Hole Diameter: |
| 0.562 inches all ends |
| Second Connection Face To Centerline Distance: |
| 4.875 inches |
| Bolt Circle Diameter: |
| 5.500 inches all ends |
| Flange Face Design: |
| Plain all ends |
| Material: |
| Nickel alloy flow control device |
| Style Designator: |
| Err-090 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 4820-01-026-2245

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0