NSN 4820-01-026-6944



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-01-026-6944 **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: Piston **Disk Loading Method:** Spring **Maximum Operating Temp:** 160.0 degrees fahrenheit single response **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube 1st end **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.437 inches 1st end **Outside Diameter Tube Accommodated:** 0.250 inches 1st end Material: Aluminum alloy 2024 **Material Specification:** Qq-a-225/6, t4 federal specification single material response Media For Which Designed: Nitrogen, gaseous 2nd response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Style Designator:** Err-090 **Thread Series Designator:** Unf 1st end Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A046b0

NSN 4820-01-026-6944

Safety Relief Valve - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.