Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-027-3212

# Thread Class:

3a all ends

**Thread Direction:** 

Right-hand all ends

# Flow Control Device:

Poppet

## **Disk Loading Method:**

Spring

#### Maximum Operating Temp:

160.0 degrees fahrenheit 2nd response

#### **Connection Style:**

Flareless all ends

#### Valve Operation Method:

Automatic

#### **Connection Type:**

Threaded external tube all ends

**Mounting Position:** 

Horizontal or vertical

### Maximum Operating Pressure:

300.0 pounds per square inch single response

## Thread Size:

0.750 inches all ends

## Seat Angle:

12.0 degrees 1st end

#### Material:

Stainless steel seat

#### **Material Specification:**

Mil-s-7720 military specification single material response body

#### Media For Which Designed:

Fuel/oil, hydrocarbon single response

#### Surface Treatment:

Passivate

# Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

# Style Designator:

Straight thru

# **Thread Series Designator:**

Unjf all ends

Shelf Life:

N/a

# Unit Of Measure:

---

# NSN 4820-01-027-3212

Check Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-s-7720 spec.

