NSN 4820-01-030-4941



Check Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-01-030-4941 **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 160.0 degrees fahrenheit 2nd response **Connection Style:** Flareless 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube 1st end **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 15.0 pounds per square inch single response **Thread Size:** 0.500 inches 2nd end Seat Angle: 12.0 degrees 1st end Material: Steel comp 440c seat **Material Specification:** Qq-s-763, class 440c federal specification single material response flow control device Media For Which Designed: Fuel/oil, hydrocarbon single response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 2 military specification single treatment response **Style Designator:** Straight thru **Thread Series Designator:** Unjf 1st end Shelf Life: N/a

Unit Of Measure:

NSN 4820-01-030-4941

Check Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.