NSN 4820-01-032-4460

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-032-4460

Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
40.6 gallons per minute
Maximum Operating Temp:
406.0 degrees fahrenheit 3rd response
Connection Style:
G9 plain, optional en (pipe) 2nd end
Valve Operation Method:
Manual
Connection Type:
Threaded internal pipe 2nd end
Valve Size:
1.000 inches
Maximum Operating Pressure:
300.0 pounds per square inch 3rd response
Thread Size:
1.000 inches 2nd end
Opening Pressure Setting:
150.0 pounds per square inch
First Connection Face To Centerline Distance:
1.625 inches
Second Connection Face To Centerline Distance:
2.6875 inches
Material:
Copper alloy body
Media For Which Designed:
Oil 2nd response
Style Designator:
Err-090
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a

NSN 4820-01-032-4460

Safety Relief Valve - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A046b0