NSN 4820-01-032-6549

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-032-6549 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 160.0 degrees fahrenheit 2nd response **Connection Style:** Flared (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 20.0 pounds per square inch single response **Thread Size:** 0.438 inches all ends Seat Angle: 37.0 degrees 1st end Material: Steel comp 303 flow control device **Material Specification:** Qq-a-225/6, alloy 2024, 5351 federal specification single material response body Media For Which Designed: Fuel/oil, hydrocarbon single response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 2 military specification single treatment response **Style Designator:** Angle **Thread Series Designator:** Unjf all ends Shelf Life: N/a

Unit Of Measure:

NSN 4820-01-032-6549

Check Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.