NSN 4820-01-033-0022

Globe Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-033-0022

2.000 inches 1st end Flow Control Device: Disk Connection Style: Socket 1st end Valve Operation Method: Electric motor Connection Type: Unthreaded internal pipe 1st end Features Provided: Bonnet packing Maximum Operating Pressure: 10800.0 pounds per square inch single response Special Features: Socket weld Material: Steel stem Material Specification: Cobalt-chromium-tungsten, alloy no. 6, stellite div. Cabot corporation mfr ref single material response flow control device Media For Which Designed: Water-oil-gas single response Shelf Life: N/a Unit Of Measure: Demilitarization:
Disk Connection Style: Socket 1st end Valve Operation Method: Electric motor Connection Type: Unthreaded internal pipe 1st end Features Provided: Bonnet packing Maximum Operating Pressure: 10800.0 pounds per square inch single response Special Features: Socket weld Material: Steel stem Material Specification: Cobalt-chromium-tungsten, alloy no. 6, stellite div. Cabot corporation mfr ref single material response flow control device Media For Which Designed: Water-oil-gas single response Shelf Life: N/a Unit Of Measure:
Connection Style: Socket 1st end Valve Operation Method: Electric motor Connection Type: Unthreaded internal pipe 1st end Features Provided: Bonnet packing Maximum Operating Pressure: 10800.0 pounds per square inch single response Special Features: Socket weld Material: Steel stem Material Specification: Cobalt-chromium-tungsten, alloy no. 6, stellite div. Cabot corporation mfr ref single material response flow control device Media For Which Designed: Water-oil-gas single response Shelf Life: N/a Unit Of Measure:
Socket 1st end Valve Operation Method: Electric motor Connection Type: Unthreaded internal pipe 1st end Features Provided: Bonnet packing Maximum Operating Pressure: 10800.0 pounds per square inch single response Special Features: Socket weld Material: Steel stem Material Specification: Cobalt-chromium-tungsten, alloy no. 6, stellite div. Cabot corporation mfr ref single material response flow control device Media For Which Designed: Water-oil-gas single response Shelf Life: N/a Unit Of Measure:
Valve Operation Method: Electric motor Connection Type: Unthreaded internal pipe 1st end Features Provided: Bonnet packing Maximum Operating Pressure: 10800.0 pounds per square inch single response Special Features: Socket weld Material: Steel stem Material Specification: Cobalt-chromium-tungsten, alloy no. 6, stellite div. Cabot corporation mfr ref single material response flow control device Media For Which Designed: Water-oil-gas single response Shelf Life: N/a Unit Of Measure:
Electric motor Connection Type: Unthreaded internal pipe 1st end Features Provided: Bonnet packing Maximum Operating Pressure: 10800.0 pounds per square inch single response Special Features: Socket weld Material: Steel stem Material Specification: Cobalt-chromium-tungsten, alloy no. 6, stellite div. Cabot corporation mfr ref single material response flow control device Media For Which Designed: Water-oil-gas single response Shelf Life: N/a Unit Of Measure:
Connection Type: Unthreaded internal pipe 1st end Features Provided: Bonnet packing Maximum Operating Pressure: 10800.0 pounds per square inch single response Special Features: Socket weld Material: Steel stem Material Specification: Cobalt-chromium-tungsten, alloy no. 6, stellite div. Cabot corporation mfr ref single material response flow control device Media For Which Designed: Water-oil-gas single response Shelf Life: N/a Unit Of Measure:
Unthreaded internal pipe 1st end Features Provided: Bonnet packing Maximum Operating Pressure: 10800.0 pounds per square inch single response Special Features: Socket weld Material: Steel stem Material Specification: Cobalt-chromium-tungsten, alloy no. 6, stellite div. Cabot corporation mfr ref single material response flow control device Media For Which Designed: Water-oil-gas single response Shelf Life: N/a Unit Of Measure:
Features Provided: Bonnet packing Maximum Operating Pressure: 10800.0 pounds per square inch single response Special Features: Socket weld Material: Steel stem Material Specification: Cobalt-chromium-tungsten, alloy no. 6, stellite div. Cabot corporation mfr ref single material response flow control device Media For Which Designed: Water-oil-gas single response Shelf Life: N/a Unit Of Measure:
Bonnet packing Maximum Operating Pressure: 10800.0 pounds per square inch single response Special Features: Socket weld Material: Steel stem Material Specification: Cobalt-chromium-tungsten, alloy no. 6, stellite div. Cabot corporation mfr ref single material response flow control device Media For Which Designed: Water-oil-gas single response Shelf Life: N/a Unit Of Measure:
Maximum Operating Pressure: 10800.0 pounds per square inch single response Special Features: Socket weld Material: Steel stem Material Specification: Cobalt-chromium-tungsten, alloy no. 6, stellite div. Cabot corporation mfr ref single material response flow control device Media For Which Designed: Water-oil-gas single response Shelf Life: N/a Unit Of Measure:
10800.0 pounds per square inch single response Special Features: Socket weld Material: Steel stem Material Specification: Cobalt-chromium-tungsten, alloy no. 6, stellite div. Cabot corporation mfr ref single material response flow control device Media For Which Designed: Water-oil-gas single response Shelf Life: N/a Unit Of Measure:
Special Features: Socket weld Material: Steel stem Material Specification: Cobalt-chromium-tungsten, alloy no. 6, stellite div. Cabot corporation mfr ref single material response flow control device Media For Which Designed: Water-oil-gas single response Shelf Life: N/a Unit Of Measure:
Socket weld Material: Steel stem Material Specification: Cobalt-chromium-tungsten, alloy no. 6, stellite div. Cabot corporation mfr ref single material response flow control device Media For Which Designed: Water-oil-gas single response Shelf Life: N/a Unit Of Measure:
Material: Steel stem Material Specification: Cobalt-chromium-tungsten, alloy no. 6, stellite div. Cabot corporation mfr ref single material response flow control device Media For Which Designed: Water-oil-gas single response Shelf Life: N/a Unit Of Measure:
Steel stem Material Specification: Cobalt-chromium-tungsten, alloy no. 6, stellite div. Cabot corporation mfr ref single material response flow control device Media For Which Designed: Water-oil-gas single response Shelf Life: N/a Unit Of Measure:
Material Specification: Cobalt-chromium-tungsten, alloy no. 6, stellite div. Cabot corporation mfr ref single material response flow control device Media For Which Designed: Water-oil-gas single response Shelf Life: N/a Unit Of Measure:
Cobalt-chromium-tungsten, alloy no. 6, stellite div. Cabot corporation mfr ref single material response flow control device Media For Which Designed: Water-oil-gas single response Shelf Life: N/a Unit Of Measure:
Media For Which Designed: Water-oil-gas single response Shelf Life: N/a Unit Of Measure:
Water-oil-gas single response Shelf Life: N/a Unit Of Measure:
Shelf Life: N/a Unit Of Measure:
N/a Unit Of Measure:
Unit Of Measure:
Demilitarization:
Demilitarization:
No
Fiig:
A046b0